arXiv:2310.04135v1 [quant-ph] 6 Oct 2023

Quantum communications feasibility tests over a UK-Ireland 224-km undersea link

Ben Amies-King^{1,†}, Karolina P. Schatz^{1,†}, Haofan Duan^{1,†}, Ayan Biswas¹, Jack Bailey², Adrian Felvinti²,

Jaimes Winward², Mike Dixon², Mariella Minder^{1,3}, Rupesh Kumar¹, Sophie Albosh¹, Marco Lucamarini¹

¹School of Physics, Engineering & Technology and York Centre for Quantum Technologies,

Institute for Safe Autonomy, University of York, YO10 5FT York, U.K.

²euNetworks Fiber UK Limited, 5 Churchill Place, London, E14 5HU, U.K.

³Department of Electrical Engineering, Computer Engineering and Informatics,

karolina.schatz@york.ac.uk (K.P.S), marco.lucamarini@york.ac.uk (M.L.)

[†]These authors contributed equally to this work.

The future quantum internet will leverage existing communication infrastructures, including deployed optical fibre networks, to enable novel applications that outperform current information technology. In this scenario, we perform a feasibility study of quantum communications over an industrial 224 km submarine optical fibre link deployed between Southport in the United Kingdom (UK) and Portrane in the Republic of Ireland (IE). With a characterisation of phase drift, polarisation stability and arrival time of entangled photons, we demonstrate the suitability of the link to enable international UK-IE quantum communications for the first time.

I. INTRODUCTION

Quantum key distribution (QKD) [1–4] aims to enable confidential communications with security guaranteed by the laws of physics, even in the presence of an eavesdropper with superior computational ability. Its most common implementation utilises fibre optical channels with C-band light carrying information encoded in polarisation [5] or optical phase [6]. The former degree of freedom is advantageous due to the ease of establishing and maintaining a stable reference between the parties [7, 8], even with passive transmitters [9]. The latter enables beneficial rate-distance scaling via 'twin-field' (TF) QKD [10] and has led to a sequence of QKD demonstrations over record-breaking distances in recent years [11–14]. QKD can also be achieved by the distribution of entanglement between distant users, followed by local measurements [15, 16]. In addition to QKD, entanglement is a fundamental resource for other quantum information protocols, e.g., quantum teleportation [17–19].

To date, there have been several QKD field trials on deployed fibre infrastructure worldwide [20-26] although only a limited number demonstrate long-distance international quantum communications [27]. Of these, only two use a submarine communication link [28, 29], which still represents a largely unexplored scenario. For undersea optical fibres, the longest geographical distance achieved so far, between Italy and Malta, is of 96 km [28] or 192 km in a loop-back configuration [29].

In this work we perform a series of experiments to assess the suitability of a 224 km submarine fibre link for quantum communications protocols. The link, denominated 'Rockabill', has been deployed by the company euNetworks [30] between their Cable Landing Stations (CLSs) in Southport (UK) and Portrane (IE). It features low loss (0.17 dB/km on average) to enable classical communications between the two endpoints without resorting to intermediate optical repeaters, and low latency to serve time-hungry customers e.g. from the financial sector. Hence, the Rockabill link is a natural candidate to connect the UK and IE via quantum communications. However, this requires experimental verification, to rule out the uncertainty entailed by prior simulations, reported below.

Within the duration of a month, we perform a series of tests to characterise the UK-IE channel for quantum communications. We first carry out a measurement of the relative phase drift between two paired fibres in the channel. This is the relevant degree of freedom in applications like TF-QKD and time-frequency reference dissemination [31]. Secondly, we characterise the impact of polarisation drift on the Quantum Bit Error Rate (QBER) of a proof-ofconcept prepare-and-measure polarisation-based QKD setup operating at the single photon level. Polarisation drift, inherent to optical fibres, leads to increased QBER and necessitates periodic realignment of the system. We explore the timescales over which polarisation is sufficiently stable and attempt to gain insight into the origins of the most prominent noise features. Finally, we demonstrate coincidence measurements of entangled photon pairs generated by a compact commercial single photon source [32] in the presence of significant channel noise, which is a step towards a record-distance entanglement distribution. Previous implementations of entanglement distribution have been achieved over a maximum total distance of 248 km over terrestrial deployed fibre [27], which is considerably shorter than the $448 \text{ km} (2 \times 224 \text{ km})$ travelled by the two photons in our experiment.

With the combination of these experiments, we report a unique in-the-field feasibility study with wide-ranging implications for a variety of quantum communications protocols, particularly QKD.

Cyprus University of Technology, Limassol, 3036, CY

^{*}Correspondence: ben.amies-king@york.ac.uk (B.A-K.),

II. MATERIALS AND METHODS

A. The Rockabill link

In this work we utilise two equivalent fibre pairs (identified as channels 39 & 40 and 59 & 60) in the above-described submarine Rockabill link. Geographic and diagrammatic representations of the link are provided in Figure 1.



FIG. 1. Field trial and experimental setup. **a**, Geographic representation and **b**, satellite image of the field trial. The 'Rockabill' link deployed by the company euNetworks [30] is drawn as an orange line with endpoints in the cable landing stations (CLSs) of Portrane, IE, and Southport, UK. The blue dot in the top panel denotes the University of York (UoY). The whole experimental setup and its subsystems, including the SNSPDs, were moved from the UoY to the two CLSs to perform the feasibility tests. **c-e**, Subsystems of the experimental setup to characterise optical phase (top), polarisation (middle) and entangled photon pair distribution (bottom) across the UK-IE link.

The fibres under test are routed in a bundle containing several active telecommunication fibres using high-intensity signals. The link has a length of 224 km and a total effective loss per fibre of 38.1 - 38.7 dB, which equates to a remarkably low average attenuation per kilometer of approximately 0.17 dB/km. Despite this low loss coefficient of the fibres, operating at the single photon level across such high channel attenuation is challenging with infrared single photon avalanche detectors (SPADs), due to low detection efficiencies and high dark counts, unless special features are applied to the detectors [33].

In contrast, a superconducting nanowire single photon detector (SNSPD) system offers much higher detection efficiency and low dark counts at the expense of a larger footprint. We therefore set up an SNSPD system (ID281 from IDQ [34]) in Southport and use two detector channels with detection efficiencies of 93.0% and 90.5% and dark count rates less than 70 Hz per channel.

For a number of the optimisation procedures required for these experiments, the detection and actuation equipment are on opposite sides of the fibre link. To enable these remote processes, we developed and deployed a lightweight asynchronous web server to bridge between Portrane and Southport. In principle, classical communication could be performed via conventional data signals sent over the fibre link itself. However, this would introduce noise into the measurements, due to scattering effects from bright multiplexed signals, thus making the option of a separate server preferable.

B. Loss and noise characterisation

An extensive attenuation and reflection characterisation of the submarine fibre channel had been provided to us by euNetworks for the channels 39 and 40, stating 38.65 and 38.14 dB as the channel insertion losses respectively. We verify the combined loss figure for both channels ourselves by connecting the two fibre outputs in Portrane, effectively creating a loop from Southport back on itself. In this loop-back configuration, we send 10 mW of light from a laser into the first fibre, which is looped-back into a second fibre and measured on an optical power metre, showing a total loss of 76 dB. For the other pair of channels 59 and 60, no prior characterisation was available. We determined the insertion loss by sending 5 mW of light from Portrane through the fibres and measuring the output at Southport. This gave us an estimation of 38.2 and 38.6 dB loss for channels 59 and 60, respectively, comparable to the attenuation of the other fibre pair.

In addition to losses, the presence of bright active fibres in the same bundle as our experimental fibre lead to significant cross talk in the channels and consequently an unexpectedly high noise floor. We performed a number of tests to characterise the source of noise and its influence on the quantum signals. During these tests, the entrance to the channels in Portrane were terminated, and different instruments were connected in the darkened CLS in Southport to investigate the light arriving there.

Firstly, we record a 12 hour-long overnight measurement of the single photon count rate on a single channel using a SPAD. The measurement includes sunset as well as sunrise and shows a remarkable long-term stability of the noise amplitude (standard deviation <0.5%). Next, we perform a coarse and a fine sweep of the noise wavelength spectrum using a tunable optical wavelength filter directly before the SNSPD, at bandwidths of 125 and 100 GHz. Results of the coarse sweep for two selected channels can be seen in the inset to Figure 6. The spectrum is not indicative of a typical scattering process or thermal emission, instead it resembles a convolution of several peaks of varying amplitude and width. This test also serves to exclude the possibility that stray light enters the exposed fibre within the CLS itself, since disconnecting the fibre channel from the measurement setup, while leaving all the other fibres in place, removes all counts on the SNSPD apart from the typical 70 Hz detector dark counts (see grey line in the Figure 6 inset). Furthermore, a quick investigation using a manual polarisation controller followed by a linear polariser shows that the noise in its entirety does not have a preferred polarisation orientation, whereas individual peaks isolated with the tunable optical filter can be found to be at least partially polarised.

Combining the above results leads us to the conclusion that the noise is indeed caused by stray photons from other active fibres entering our channels under test, most likely from back-reflection of bright signals leaking into the tested channels close to the detection setup in Southport. We find such a background to be present in all channels arriving at the CLS, but its magnitude varies significantly from channel to channel, most likely depending on physical proximity to the most active fibres. For the two fibre pairs used in this work, we measure count rates ranging from 120 kHz to 410 kHz when permitting the entire spectrum to the SNSPD. Introducing optical filters on the order of 1 nm bandwidth significantly mitigates this noise and makes our quantum measurements possible. Effective dark counts for the single photon experiments reported here range from 90 Hz to as high as 2.2 kHz, depending on the chosen central wavelength of the filters utilised.

C. Optical phase characterisation

For the first experiment, a 1 kHz linewidth laser at 1550 nm is coupled into the fibre pair via a 50:50 beamsplitter in Portrane, as shown in Figure 1c. One output of the beamsplitter (arm 1) is connected to the channel via an electronic polarisation controller (EPC1) and both outputs have an electrical variable optical attenuator (EVOA) used to enable polarisation alignment. In Southport, the channel that is not connected via EPC1 in Portrane (arm 2) enters an identical EPC (EPC2). Both arms then pass through linear polarisers before interfering on a beamsplitter. The beamsplitter outputs are measured on high-sensitivity photodiodes at a sampling rate of 2 MS/s.

Before running an acquisition, polarisation is aligned to optimise interference visibility. A gradient descent algorithm maximises the power on the photodiodes in the absence of interference, after fully attenuating light from the complementary arm. This process is done individually and sequentially per channel using the EPCs.

A similar process is used to obtain the detector noise shown in subplot \mathbf{b} of Figure 2; with one arm fully attenuated and polarisation aligned, an acquisition is run in the absence of any interference and thus without phase noise from the channel.

D. Polarisation characterisation

In order to characterise the impact of channel polarisation drift on QBER, the setup is modified to include only a single fibre in the undersea channel. Known polarisation states are prepared at the transmitter using EPC1 and a polarimeter, connected to the now vacant end of the 50:50 beamsplitter. The desired polarisation state is attained through a gradient descent algorithm. Polarisation alignment between Southport (receiver) and Portrane (transmitter) is performed by preparing a horizontal state at Portrane and then maximising the extinction ratio of the optical power at the two outputs of the PBS in Southport using EPC2. This process is performed with classical light with optical power in the order of hundreds of nanowatts. Once alignment is complete, the desired state for each measurement can be prepared in Portrane based on the polarimeter reading.

Both state preparation and alignment introduce experimental errors due to the relatively high tolerance in the alignment algorithms, which is made necessary by the low voltage granularity that the EPCs can be addressed with. In the case of state preparation, the alignment algorithm terminates once the prepared state is less than 3° (0.05 rad) from the true state on the Poincaré sphere as measured by the polarimeter. For the detector alignment, the extinction ratio between the two outputs of the PBS is 25 dB, which would ideally generate a base QBER of ~0.3%. However, based on the observed performance of the EPCs, achieving such an alignment requires running the optimisation for a long time. We limit the execution time of the descent-QBER algorithm to less than a minute, which returned an average base QBER ~1.6%, still well within the tolerance of QKD.

Firstly, we characterise the long-term polarisation drift over the course of nearly 14 hours using the classical photodetectors.

In order to determine the channel's QBER for the four polarisation states used in the BB84 protocol, we attenuate the power launched into the channel to the single photon level after alignment. In this regime, the continuous wave laser light is set to 128 pW, which is equivalent in power to sending single photon pulses of exactly $\mu = 1$ at a repetition rate of 1 GHz. Our laser is attenuated via a series of electrical variable optical attenuators (EVOAs) to achieve the desired launch power for $\mu = 1$, whilst the output power of the laser itself is regulated via an internal feedback system. We obtain the true power launched into the channel by measuring the attenuation of each EVOA and the optical power directly before the final EVOA. Additional measurements at a fraction of single photon power are also performed to explore amplitude-varied state generation in relation to the decoy states technique [35–37].

After the desired optical power is achieved, polarisation maintaining micro-electromechanical systems (MEMS) optical switches are used to redirect the light from the classical detectors to the SNSPD channels. The two SNSPD channels are connected to a time tagger, which records the single photon count rates for 300 s per measurement.

E. Distribution of photon pairs characterisation

In this feasibility test, we explore the channel's capability to distribute photon pairs under the aspect of quantum entanglement. For this, we adopt a subsystem of the setup where the laser of the previous test is replaced by a compact source of entangled photon pairs (EPS, OZ Optics 'Ruby') with outputs connected to two parallel, though distinct, fibres of the UK-IE channel.

Photon pairs are launched from Portrane CLS into the two 224 km fibres towards the Southport CLS, where they are detected with the SNSPDs connected to a time tagger. From the time tags, we reconstruct the photons' arrival times and identify single and coincidence counts.

The EPS produces polarisation entangled photon pairs, created via spontaneous parametric downconversion (SPDC) in an auto-balanced displacement interferometer [38]. The interferometer consists of two 20 mm-long type-0 phasematched periodically poled lithium niobate (PPLN) crystals, pumped by a 780 nm laser. Signal and idler single photons are created in the maximally entangled Bell state $|\Phi^+\rangle = (|HH\rangle + |VV\rangle)/\sqrt{2}$ with a fidelity >98%.

The source's wavelength spectrum exhibits a full width at half maximum of approximately 60 nm, centred around 1560 nm. Energy conservation requirements dictate that the entangled photons are correlated in wavelength and equidistant from 1560 nm, in this case with the idler at higher and the signal at lower wavelengths.

In Southport, optical filters centred at 1550.1 nm and 1569.3 nm with a pass band of Δ =1.39 nm are used to isolate entangled pairs. This both reduces the time-of-flight induced broadening of our measured photon arrival times due to chromatic dispersion and combats the cross talk in the channel. Note that the idler side experiences roughly 5 dB of additional attenuation compared to the signal channel due to a high insertion loss optical filter, which is reflected in the detected count rate. We take advantage of the fact that the noise spectrum has a minimum around 1570 nm for the idler detection, which coincidentally puts the signal wavelength at the conventional telecom wavelength of 1550 nm. Even so, in this experiment, the link noise is comparable to the signal amplitude, see Section II B.

Since the SNSPD efficiency is polarisation-dependent, we also perform a polarisation alignment procedure to maximise the probability of detecting paired photons. This procedure consists of blocking one half of the source interfer-



FIG. 2. Relative phase drift of the fibre pair 39 and 40 of the Rockabill link. **a**, 0.5 s of the phase drift of the channel. **b**, Power spectral density (PSD) of the phase noise of the channel (blue), with detector noise (orange) plotted for comparison.

ometer to produce the non-entangled two-photon state $|\Psi\rangle = |HH\rangle$ and using manual polarisation controllers to align this state to the SNSPD's maximum efficiency state. Due to the very low absolute count rates arriving in Southport, this optimisation cannot be performed reliably, which results in small discrepancies between the two measurements taken here.

III. RESULTS

A. Optical phase characterisation

The results of the relative phase drift measurement over the pair of fibres in the Rockabill link are shown in Figure 2. Subplot **a** shows a 0.5 s excerpt of the wrapped phase drift of the fibre pair, with clear complementarity between the two lines, which correspond to the two detectors at the outputs of the interfering beamsplitter. This is signature of the first-order interference taking place over the whole channel length. The phase power spectral density (PSD) of the phase drift over 96 s is plotted in subplot **b**, along with the corresponding phase PSD of the detector in the absence of channel phase noise.

Both subplots show a consistent periodic phase fluctuation at a frequency of 100 Hz, with magnitude of a little under $\frac{\pi}{2}$. Aside from this peak, and a smaller peak at around 125 Hz, the phase noise spectrum exhibits a roll-off between 10 Hz and 1 kHz, above which frequency it quickly converges to the detector noise. This is around two orders of magnitude lower in frequency than the typical upper limit of absolute phase drift of a fibre [39], a phenomenon that agrees with previously observed data and underlines the attractiveness of submarine channels for QKD purposes.

These results are promising, as phase drifts at such low frequencies can easily be compensated through various phase stabilisation techniques implemented in either hardware [12, 40] or software [39].



FIG. 3. Long-term polarisation drift of the channel, over 14 hour overnight.

B. Polarisation characterisation

The polarisation drift of the channel is shown in Figure 3. The measurement was performed over the course of 14 hours, between 19:35 on 5/7/2023 to 09:35 on 6/7/2023. From the figure, it is apparent that the data remains stable for about 9 hours, until around 04:30. The data allows us to approximately extract interference visibility and hence QBER, with the latter being between 3.0% and 6.7%, well within the tolerance limits of QKD. At around 04:30, the polarisation starts to drift markedly, possibly due to the activation of the air conditioning system in one of the CLSs, returning an approximate QBER above 10%. This value does not change significantly for the remainder of the measurement. While it is too large for the transmission of a quantum key, it only occurs after about 9 hours of unattended operations. This shows a remarkable polarisation stability of the channel, not uncommon in undersea fibres. It would be straightforward to bring the polarisation back to its initial value by repeating the alignment procedure. Our data shows that the alignment procedure would only need to be repeated on an hour scale, which greatly simplifies the implementation of future quantum communications protocols on this channel.

As explained in Section II D, after a first characterisation of the polarisation over long timescales using bright light and sensitive power meters, we perform measurements over 300 s with the intensity of light reduced to the single photon level and received by single-photon detectors. This provided us with a more accurate QBER estimation, which can be used to assess the suitability of the Rockabill link for QKD.

The results are reported in Figure 4, showing the measured count rates and QBER. In sub-panels **a-h**, referring to preparing and measuring the polarisation basis H/V, the photon flux decreases from left to right. Correspondingly, count rates decrease and QBER increases on average, as expected. The average QBER when $\mu = 1$ is $2.98 \pm 0.54\%$ for a $|H\rangle$ preparation $1.55 \pm 0.15\%$ for a $|V\rangle$ preparation. Even with the lowest launch power, $\mu = 0.4$, the average QBER is $4.26 \pm 0.67\%$ and $8.49 \pm 0.96\%$ for the horizontal and vertical polarization states, respectively, which are within the expectations for a 224-km optical fibre.

To check the polarisation alignment between the four states of the BB84, we also perform a measurement in the H/V basis after preparing the initial states in the D/A basis. The results are shown in sub-panels **i** and **j** of Figure 4 for a photon flux $\mu = 1$. In the ideal case, the QBER would be aligned around the 50% value. Our measured QBER is not far from this condition, especially for the preparation of the $|H\rangle$ state (sub-panel **i**). The non-ideal initial state preparation is also apparent from the fluctuations displayed in diagrams **f**, **i** and **j**, on a minute scale, which we attribute to the free evolution of an unwanted elliptical component in the initial polarization states.

The values reported in Figure 4 for a varying photon flux can be used to experimentally infer the asymptotic secret key rate (SKR) of a QKD system clocked at 1 GHz and running the decoy-state BB84 protocol over the Rockabill link. After plugging the values of photon flux, count rates and QBER in the decoy-state equations [41], we obtain the SKR shown with an orange diamond in Figure 5. It corresponds to 2.93×10^{-6} bit/clock and is obtained when signal and decoy states photon fluxes are equal to 0.6 and 0.5, respectively. It is expected that this SKR can be considerably improved by optimising the initial values of the photon flux. The optimisation should also lead to a positive SKR in the more challenging finite-size scenario, which we leave for future investigations.

Using $\mu = 0.6$ and the parameters of the Rockabill link, we also report a simulation of the SKR for a variable distance between the end points Alice and Bob. The result is given by the blue line in Figure 5. On one hand, it shows that the simulation matches our experimental observation; on the other hand, it also shows how challenging the experiment was and underlines the necessity to conduct an experimental test. The length of the Rockabill link falls in the region where the SKR starts to roll over and goes to zero with a steep slope, leading to a zero SKR at



FIG. 4. Total count rates (blue) and QBER (red) for different quantum states prepared in Portrane, as measured in Southport. Plots **a**, **c**, **e**, **g** correspond to a preparation of the state $|H\rangle$ measured in the rectilinear basis H/V; plots **b**, **d**, **f**, **h** are similar, but for the state $|V\rangle$. Plots **i**, **j** correspond to states D and A prepared, respectively, measured in the rectilinear basis H/V. The first and last column were generated with photon flux $\mu = 1$, whereas columns 2-4 depict states at μ equal to 0.6, 0.5 and 0.4 respectively.

233 km. This is only 9 km away from our experimental point. To put this figure into context, it would suffice to add one additional beam splitter in Bob's setup to add 3 dB of loss to the channel and result in a zero SKR.

C. Photon pair distribution characterisation

Using the entanglement analyser built in our setup and described in Section IIE and Figure 1 \mathbf{e} , we record two sets of data which accumulate single photon detection events over 12 hours each, time tagged to a resolution of 1 ps with a combined instrument jitter of the order of 50 ps. After traversing the submarine channels, the single count rates of each individual channel are only a few hundred Hz above the background, resulting in a signal to noise ratio below one for the noisier 1550.1 nm channel. Results are given for both sets, but only the better aligned measurement is discussed in detail in the following.

In the better aligned measurement, the signal channel at 1550.1 nm records a single count rate of 2703 Hz over a background rate of 2171 Hz, whereas the much lower noise idler channel at 1569.3 nm produces a total count rate of 258 Hz over 88 Hz background.

Figure 6 illustrates the difference in photon arrival time on both channels compared to a common reference clock for the better aligned data set. A fixed offset of 113 ns is present due to minor channel length differences (introduced mainly by our instruments), but the peak corresponding to simultaneously produced pair photons is clearly visible. Photon pairs can be identified in a coincidence window of 12 ns, which matches the expected broadening through chromatic dispersion after 224 km. The observed number of accidental photon coincidences corresponds to the statistically expected value based on the individual count rates. The coincidences rise above this baseline with a coincidence to accidentals ratio of 1.92 in the better aligned measurement and 1.80 in the other. The presence of a clear peak in Figure 6 is promising and paves the way for future stronger demonstrations of entanglement distribution, ultimately prevented in this experiment by the excessive noise described above. Solutions to further filter the noise and detect entanglement on the same optical link are currently being vetted.



FIG. 5. Simulation of the secret key rate (SKR, blue solid line) with the parameters of the UK-IE field trial (inset) and our experimental point (orange empty diamond). The distance of the field trial between Alice, in the Portrane CLS, and Bob, in the Southport CLS, is 224 km, only 9 km shorter than the maximum distance providing a positive SKR (233 km). Parameters: η_{det} : detection efficiency (SNSPD); η_{rec} : efficiency of the receiver; p_{dark} : dark counts; p_{stray} : background photons from the channel; e_{opt} : optical noise; μ : mean photon number; f_{clock} : clock rate of the simulated system.

IV. DISCUSSION

We planned, designed and implemented an experimental campaign aimed at characterising the suitability for quantum communications of the 'Rockabill' submarine optical link, deployed by the company euNetworks between Portrane, IE, and Southport, UK. During the tests, we measured a continuous phase drift, reported in Figure 2, significantly below the expected values for typical optical fibre and in line with previous observations of submarine fibre links. The present phase variations are within the range of common phase stabilisation techniques, which promises successful implementation of phase-based QKD protocols.

The polarisation behavior of the current link (Figure 3) is also promising for the implementation of a polarisation encoded BB84 QKD protocol. The polarisation remains stable over the course of about 90 minutes. After this time it is necessary to re-align the system to assure continuous operation, which we consider straightforward given the long lapse of time. Over this period of time, the QBER remains below 4.26% for the horizontal state $|H\rangle$ and below 8.49% for the vertical state $|V\rangle$, both of which are sufficiently low values for the implementation of this QKD protocol. This made it possible to extract a positive SKR from the data using, in particular, the two μ values 0.6 (signal state) and 0.5 (decoy state). It is worth mentioning that other values of the photon flux, e.g. 1 for signals and 0.5 for decoys, would not lead to a positive SKR, showing a non-trivial role played by the selected parameters in the obtained results.

Lastly, we detect the presence of entangled photons after a combined propagation distance of 448 km covered by the two photons in separate deployed optical fibres. The entangled pairs are identified with a signal to noise ratio of at most 1.92 (Figure 6). This constitutes a step towards an ultra-long fibre based entanglement distribution, which so far has been performed over 248 km in deployed fibre [27] and 300 km in a laboratory environment [42]. A number of measures can be taken to improve the pair detection rate in order to promote entanglement visibility. This includes, but is not limited to: noise reduction, compensation for chromatic dispersion for improved temporal filtering, improved system alignment with a laser for optimised detection, and utilisation of the full EPS spectrum for improved source brightness.

V. CONCLUSIONS

The performed experiments highlight the excellent potential of the euNetworks 224 km submarine optical fibre to connect the United Kingdom and Ireland via quantum communications for the first time. Our results show that



FIG. 6. Histogram of the time delays between consecutive photon detections at the end of the two submarine channels. Pair photons from the EPS arrive with a fixed relative delay of 113 ns at a signal to noise ration of 1.92, computed over the indicated red 12 ns coincidence window. The green lines indicates an exemplary coincidence window including only accidentals. The inlay shows the typical spectrum of the stray photon noise present in the channel, with the dashed lines indicating the wavelengths chosen for the EPS measurement.

protocols ranging from QKD to entanglement distribution, exploiting optical phase or polarisation for encoding, are feasible across the link if high-efficiency low-noise single photon detectors are employed. These preliminary experiments pave the way to others that are closer to a real-world implementation. Given the industrial nature of the link used in the present set of experiments, this prospect is particularly desirable and is planned for the near future.

ACKNOWLEDGMENTS

We acknowledge invaluable help with the logistics from Chris Silk and Alex Van Der Arend, and the support received by the technical team of the Institute for Safe Autonomy. Funding has been provided through the partnership resource scheme of the EPSRC Quantum Communications Hub grant (EP/T001011/1). The authors declare no conflict of interest. The funders had no role in the design of the study; in the collection, analyses, or interpretation of data; in the writing of the manuscript; or in the decision to publish the results.

- C. H. Bennett and G. Brassard, Quantum cryptography: Public key distribution and coin tossing, Theor. Comp. Sci. Theoretical Aspects of Quantum Cryptography – celebrating 30 years of BB84, 560, 7 (2014).
- [2] N. Gisin, G. Ribordy, W. Tittel, and H. Zbinden, Quantum cryptography, Rev. Mod. Phys. 74, 145, publisher: American Physical Society.
- [3] F. Xu, X. Ma, Q. Zhang, H.-K. Lo, and J.-W. Pan, Secure quantum key distribution with realistic devices, Rev. Mod. Phys. 92, 025002.
- [4] S. Pirandola, U. L. Andersen, L. Banchi, M. Berta, D. Bunandar, R. Colbeck, D. Englund, T. Gehring, C. Lupo, C. Ottaviani, J. L. Pereira, M. Razavi, J. Shamsul Shaari, M. Tomamichel, V. C. Usenko, G. Vallone, P. Villoresi, and P. Wallden, Advances in quantum cryptography, Adv. Opt. Photon. 12, 1012 (2020).
- [5] C. H. Bennett, F. Bessette, G. Brassard, L. Salvail, and J. Smolin, Experimental quantum cryptography, Journal of Cryptology 5, 3 (1992).
- [6] C. H. Bennett, Quantum cryptography using any two nonorthogonal states, Phys. Rev. Lett. 68, 3121 (1992).
- [7] C. Agnesi, M. Avesani, A. Stanco, P. Villoresi, and G. Vallone, All-fiber self-compensating polarization encoder for quantum key distribution, Opt. Lett., OL 44, 2398 (2019), publisher: Optica Publishing Group.

- [8] M. Avesani, C. Agnesi, A. Stanco, G. Vallone, and P. Villoresi, Stable, low-error, and calibration-free polarization encoder for free-space quantum communication, Opt. Lett., OL 45, 4706 (2020), publisher: Optica Publishing Group.
- [9] W. Wang, R. Wang, C. Hu, V. Zapatero, L. Qian, B. Qi, M. Curty, and H.-K. Lo, Fully passive quantum key distribution, Phys. Rev. Lett. 130, 220801 (2023), publisher: American Physical Society.
- [10] M. Lucamarini, Z. L. Yuan, J. F. Dynes, and A. J. Shields, Overcoming the rate-distance limit of quantum key distribution without quantum repeaters, Nature 557, 400 (2018).
- [11] M. Minder, M. Pittaluga, G. L. Roberts, M. Lucamarini, J. F. Dynes, Z. L. Yuan, and A. J. Shields, Experimental quantum key distribution beyond the repeaterless secret key capacity, Nat. Photonics 13, 334 (2019).
- [12] M. Pittaluga, M. Minder, M. Lucamarini, M. Sanzaro, R. I. Woodward, M.-J. Li, Z. Yuan, and A. J. Shields, 600-km repeater-like quantum communications with dual-band stabilization, Nat. Photon. 15, 530 (2021).
- [13] S. Wang, Z.-Q. Yin, D.-Y. He, W. Chen, R.-Q. Wang, P. Ye, Y. Zhou, G.-J. Fan-Yuan, F.-X. Wang, W. Chen, Y.-G. Zhu, P. V. Morozov, A. V. Divochiy, Z. Zhou, G.-C. Guo, and Z.-F. Han, Twin-field quantum key distribution over 830-km fibre, Nat. Photon. 16, 154 (2022), number: 2 Publisher: Nature Publishing Group.
- [14] Y. Liu, W.-J. Zhang, C. Jiang, J.-P. Chen, C. Zhang, W.-X. Pan, D. Ma, H. Dong, J.-M. Xiong, C.-J. Zhang, H. Li, R.-C. Wang, J. Wu, T.-Y. Chen, L. You, X.-B. Wang, Q. Zhang, and J.-W. Pan, Experimental twin-field quantum key distribution over 1000 km fiber distance, Phys. Rev. Lett. 130, 210801, publisher: American Physical Society.
- [15] A. K. Ekert, Quantum cryptography based on bell's theorem, Phys. Rev. Lett. 67, 661 (1991), publisher: American Physical Society.
- [16] C. H. Bennett, G. Brassard, and N. D. Mermin, Quantum cryptography without bell's theorem, Phys. Rev. Lett. 68, 557 (1992), publisher: American Physical Society.
- [17] C. H. Bennett, G. Brassard, C. Crépeau, R. Jozsa, A. Peres, and W. K. Wootters, Teleporting an unknown quantum state via dual classical and einstein-podolsky-rosen channels, Phys. Rev. Lett. 70, 1895 (1993), publisher: American Physical Society.
- [18] D. Bouwmeester, J.-W. Pan, K. Mattle, M. Eibl, H. Weinfurter, and A. Zeilinger, Experimental quantum teleportation, Nature 390, 575 (1997), number: 6660 Publisher: Nature Publishing Group.
- [19] D. Boschi, S. Branca, F. De Martini, L. Hardy, and S. Popescu, Experimental realization of teleporting an unknown pure quantum state via dual classical and einstein-podolsky-rosen channels, Phys. Rev. Lett. 80, 1121 (1998), publisher: American Physical Society.
- [20] M. Peev, C. Pacher, R. Alléaume, C. Barreiro, J. Bouda, W. Boxleitner, T. Debuisschert, E. Diamanti, M. Dianati, J. F. Dynes, S. Fasel, S. Fossier, M. FÄ¹/₄rst, J.-D. Gautier, O. Gay, N. Gisin, P. Grangier, A. Happe, Y. Hasani, M. Hentschel, H. HÄ¹/₄bel, G. Humer, T. LĤnger, M. Legré, R. Lieger, J. Lodewyck, T. LorÄ¹/₄nser, N. LÄ¹/₄tkenhaus, A. Marhold, T. Matyus, O. Maurhart, L. Monat, S. Nauerth, J.-B. Page, A. Poppe, E. Querasser, G. Ribordy, S. Robyr, L. Salvail, A. W. Sharpe, A. J. Shields, D. Stucki, M. Suda, C. Tamas, T. Themel, R. T. Thew, Y. Thoma, A. Treiber, P. Trinkler, R. Tualle-Brouri, F. Vannel, N. Walenta, H. Weier, H. Weinfurter, I. Wimberger, Z. L. Yuan, H. Zbinden, and A. Zeilinger, The SECOQC quantum key distribution network in vienna, New J. Phys. 11, 075001 (2009).
- [21] M. Sasaki, M. Fujiwara, H. Ishizuka, W. Klaus, K. Wakui, M. Takeoka, S. Miki, T. Yamashita, Z. Wang, A. Tanaka, K. Yoshino, Y. Nambu, S. Takahashi, A. Tajima, A. Tomita, T. Domeki, T. Hasegawa, Y. Sakai, H. Kobayashi, T. Asai, K. Shimizu, T. Tokura, T. Tsurumaru, M. Matsui, T. Honjo, K. Tamaki, H. Takesue, Y. Tokura, J. F. Dynes, A. R. Dixon, A. W. Sharpe, Z. L. Yuan, A. J. Shields, S. Uchikoga, M. Legré, S. Robyr, P. Trinkler, L. Monat, J.-B. Page, G. Ribordy, A. Poppe, A. Allacher, O. Maurhart, T. LĤnger, M. Peev, and A. Zeilinger, Field test of quantum key distribution in the tokyo QKD network, Opt. Express 19, 10387 (2011).
- [22] J. F. Dynes, A. Wonfor, W. W. S. Tam, A. W. Sharpe, R. Takahashi, M. Lucamarini, A. Plews, Z. L. Yuan, A. R. Dixon, J. Cho, Y. Tanizawa, J. P. Elbers, H. Greißer, I. H. White, R. V. Penty, and A. J. Shields, Cambridge quantum network, npj Quantum Information 5, 101 (2019).
- [23] D. Bacco, I. Vagniluca, B. D. Lio, N. Biagi, A. D. Frera, D. Calonico, C. Toninelli, F. S. Cataliotti, M. Bellini, L. K. Oxenløwe, and A. Zavatta, Field trial of a three-state quantum key distribution scheme in the florence metropolitan area, EPJ Quantum Technology 6, 10.1140/epjqt/s40507-019-0075-x (2019).
- [24] S. K. Joshi, D. Aktas, S. Wengerowsky, M. Lončarić, S. P. Neumann, B. Liu, T. Scheidl, G. C. Lorenzo, Željko Samec, L. Kling, A. Qiu, M. Razavi, M. Stipčević, J. G. Rarity, and R. Ursin, A trusted node-free eight-user metropolitan quantum communication network, Science Advances 6, eaba0959 (2020), https://www.science.org/doi/pdf/10.1126/sciadv.aba0959.
- [25] M. Avesani, L. Calderaro, G. Foletto, C. Agnesi, F. Picciariello, F. B. L. Santagiustina, A. Scriminich, A. Stanco, F. Vedovato, M. Zahidy, G. Vallone, and P. Villoresi, Resource-effective quantum key distribution: a field trial in padua city center, Opt. Lett. 46, 2848 (2021).
- [26] A. Wonfor, C. White, A. Lord, R. Nejabati, T. P. Spiller, J. F. Dynes, A. J. Shields, and R. V. Penty, Quantum networks in the UK, in *Metro and Data Center Optical Networks and Short-Reach Links IV*, edited by M. Glick, A. K. Srivastava, and Y. Akasaka (SPIE, 2021).
- [27] S. P. Neumann, A. Buchner, L. Bulla, M. Bohmann, and R. Ursin, Continuous entanglement distribution over a transnational 248-km fiber link, Nature Communications 13, 6134 (2022).
- [28] S. Wengerowsky, S. K. Joshi, F. Steinlechner, J. R. Zichi, S. M. Dobrovolskiy, R. van der Molen, J. W. N. Los, V. Zwiller, M. A. M. Versteegh, A. Mura, D. Calonico, M. Inguscio, H. Hübel, L. Bo, T. Scheidl, A. Zeilinger, A. Xuereb, and R. Ursin, Entanglement distribution over a 96-km-long submarine optical fiber, Proceedings of the National Academy of Sciences 116, 6684 (2019), publisher: Proceedings of the National Academy of Sciences.

- [29] S. Wengerowsky, S. K. Joshi, F. Steinlechner, J. R. Zichi, B. Liu, T. Scheidl, S. M. Dobrovolskiy, R. v. d. Molen, J. W. N. Los, V. Zwiller, M. A. M. Versteegh, A. Mura, D. Calonico, M. Inguscio, A. Zeilinger, A. Xuereb, and R. Ursin, Passively stable distribution of polarisation entanglement over 192 km of deployed optical fibre, npj Quantum Inf 6, 1, number: 1 Publisher: Nature Publishing Group.
- [30] euNetworks, https://eunetworks.com/.
- [31] C. Clivati, G. Marra, F. Levi, A. Mura, A. Xuereb, and D. Calonico, Optical frequency transfer over submarine fibers, in Conference on Lasers and Electro-Optics (2020), paper SM2N.1 (Optica Publishing Group, 2020) p. SM2N.1.
- [32] O. O. Ltd., Polarization entangled photon sources, https://www.ozoptics.com/products/ polarization-entangled-photon-sources.html.
- [33] B. Fröhlich, M. Lucamarini, J. F. Dynes, L. C. Comandar, W. W.-S. Tam, A. Plews, A. W. Sharpe, Z. Yuan, and A. J. Shields, Long-distance quantum key distribution secure against coherent attacks, Optica 4, 163 (2017), 1701.07252 [quant-ph].
- [34] IDQuantique, Id281 superconducting nanowire series.
- [35] W.-Y. Hwang, Quantum key distribution with high loss: toward global secure communication, Phys. Rev. Lett. 91, 057901 (2003).
- [36] X.-B. Wang, Beating the photon-number-splitting attack in practical quantum cryptography, Phys. Rev. Lett. 94, 230503 (2005).
- [37] H.-K. Lo, X. Ma, and K. Chen, Decoy state quantum key distribution, Phys. Rev. Lett. 94, 230504 (2005).
- [38] R. Horn and T. Jennewein, Auto-balancing and robust interferometer designs for polarization entangled photon sources, Optics Express 27, 17369 (2019).
- [39] W. Li, L. Zhang, Y. Lu, Z.-P. Li, C. Jiang, Y. Liu, J. Huang, H. Li, Z. Wang, X.-B. Wang, Q. Zhang, L. You, F. Xu, and J.-W. Pan, Twin-field quantum key distribution without phase locking, Phys. Rev. Lett. 130, 250802 (2023), publisher: American Physical Society.
- [40] C. Clivati, A. Meda, S. Donadello, S. Virzì, M. Genovese, F. Levi, A. Mura, M. Pittaluga, Z. Yuan, A. J. Shields, M. Lucamarini, I. P. Degiovanni, and D. Calonico, Coherent phase transfer for real-world twin-field quantum key distribution, Nat Commun 13, 157 (2022), number: 1 Publisher: Nature Publishing Group.
- [41] X. Ma, B. Qi, Y. Zhao, and H.-K. Lo, Practical decoy state for quantum key distribution, Phys. Rev. A 72, 012326 (2005).
- [42] T. Inagaki, N. Matsuda, O. Tadanaga, M. Asobe, and H. Takesue, Entanglement distribution over 300 km of fiber, Opt. Express 21, 23241 (2013).